# One (1) New Ford Super Duty F-550 DRW (X5H) 4WD SuperCab 192" WB 84" CA or Equivalent

All standard equipment unless altered by the following options.

**Vehicle Configuration Options** 

#### **ENGINE**

6.7L V8 TURBO DIESEL

Diesel Exhaust Fluid (DEF) tank

Manual push-button engine-exhaust braking

240 Amp Alternator

**Dual Batteries** 

#### **TRANSMISSION**

**TORQSHIFT 10-SPEED AUTOMATIC** 

#### **TIRES**

4 traction tires on the rear and 2 traction tires on the front

#### **PRIMARY PAINT**

To be determined at time of order or by dealer stock

# **SEAT TYPE**

MEDIUM EARTH GRAY, VINYL 40/MINI-CONSOLE/40 FRONT SEAT, -inc: driver's side manual lumbar

### **AXLE RATIO**

LIMITED SLIP W/4.30 AXLE RATIO

# **ADDITIONAL EQUIPMENT**

POWER EQUIPMENT GROUP- Power Locks, Remote Keyless Entry, Folding Trailer Tow Mirrors w/Power Heated Glass, manual telescoping, heated convex spotter mirror and integrated clearance lamps/turn signals, Power Front & Rear Side Windows, 1-touch up/down driver/passenger window

TRANSMISSION POWER TAKE-OFF PROVISION, -inc: mobile and stationary PTO modes

**OPERATOR COMMANDED REGENERATION** 

TRAILER BRAKE CONTROLLER

HIGH-CAPACITY TRAILER TOW PACKAGE

TRANSFER CASE SKID PLATES

**UTILITY LIGHTING SYSTEM** 

PLATFORM RUNNING BOARDS

FRONT LICENSE PLATE BRACKET

# <u>Vehicle Configuration Options (continued)</u>

CENTER HIGH-MOUNTED STOP LAMP (CHMSL)

REMOTE START SYSTEM

STEERING WHEEL-MOUNTED CRUISE CONTROL

REAR VIEW CAMERA & PREP KIT, -inc: pre-installed content includes cab wiring and frame wiring to the rear most cross member, Upfitters kit includes camera w/mounting bracket, 20' jumper wire and camera mounting/aiming instructions

110V/400W OUTLET

AMBER-WHITE LED WARNING STROBES -Cab Clearance Strobe Lights

# uivalent

Custom Knapheide Steel Service Body for for dual rear wheel 84" C.A. or Eq
Mod: 6132D5460
11' long
40" compartment height
20" depth
54" floor width
60" raised front compartment (streetside)
Revit-less rotary latches
LED surface mount taillights (with strobe capability)
Aluminum fuel fill cup
Aluminum stone guards on lower front corners of body
Standard shelving package
Mounting kit
8 – 2000 lb rated cargo ties
4-hose hook cargo area
7- Shovel storage tubs installed between body and cab
Compressor mounting plate on curbside top compartment
Flip top compartment streetside (shortened due to 60" raised compartment)
Combine first two vertical compartments curbside, overlap doors with 1/8"
Treadplate overlay floor for reinforcement
Shovel holder in cargo area
LED compartment lights
Body painted BLACK
Body completely undercoated
Completely installed on customer supplied chassis

# **Additional Accesories**

Thieman 1500 lb. steel platform liftgate 53"w x 42" d pc. 5" ramp

Vanair Reliant RS85 Hydraulic drive compressor

Hydroflow hydraulic oil cooler

3 air outlets, 1 each side and 1 in rear

LED pole light:

Pole Light Spec.

Lamp Type:LED36 Watt, 2520 LumenLamp

Dimensions:6" W x 6" Depth x 7"

HRemote Control, 150' RangePole

Dimensions: Adjustable - 4' to 9.08' - With Light Head (3.19' to 8.35' Without - 1.375" Base

Adjustable Light TowerWeight: Lamp Only - 5 Lbs Lamp and Pole - 8 LbsMeets Marine Standards for Fresh / Saltwater Use.

Total Watts: 36 wattsUV and WeatherproofVoltage: 12V DC12V DC Operation-Lighting Configuration: Wide Spot BeamAmps: 3 AmpsMounting: Telescoping Pole MountWiring: 16' Coil Cord w/ Cig Plug, Battery Clamps, or Ring Terminals

#### Note:

We will consider any class 5 in stock unit as well as a custom order, from any make, so long as it meets or exceeds the specifications listed. All specifications will be verified prior to award.