

SPECIFICATIONS---CITY OF WATERTOWN

2022 PICKUP WITH SERVICE BODY

2022 Ford F250 XL, Regular cab, two-wheel drive (4x2), with 56" C/A (cab to axle) to accommodate an eight (8) foot Knapehide or Reading Classic II service body and related options and truck accessories.

Engine: 6.2L v-8 engine with six speed torq-shift "G" transmission

Axles: 3.73:1 axle ratio

Tires: (5) LT245/75E BSW. All terrain tires on rear. All season tires on front, full size spare

Manually adjustable folding trailer tow mirrors

Integrated trailer brake controller

Platform running boards

110v/400 watt power outlet

200a alternator

Up-fitter switches

Front wheel well liners

Front wheel mud flaps/splash guards

Factory installed back up alarm

Rear view camera and prep kit

AM/FM radio

Class V receiver hitch w/2 ½" receiver tube

"Husky" brand floor liners

Interior: HD vinyl 40/20/40 bench seat; Medium earth gray

Exterior: Antimatter Blue

1 of 3

2022 Service Body

Service body to be mounted on chassis and painted to match the factory chassis color using the same factory process; i.e. base coat/clear coat. Service body to be mounted in accordance with all manufacturer's recommendations.

Model: Knapehide Model 796 or Reading Classic II U98-SW-AB eight (8) foot service body

Options:

Aluma Fill Fuel-up

One Aluma chock wheel chock holder on curb side. Provide rubber wheel chock.

Splash guards for front of service body and aluminum tail gate top edge protector

LED Compartment lighting

LED recessed S/T/T and back up lamps. A protective guard to be in rear body compartments to protect lights from damage.

Amber rear strobes—recessed strobes to match style of S/T/T/ lamps. Connect to up-fitter switch in cab. Switch to be marked accordingly.

Side mounted ladder rack on curb side painted to match chassis.

Spray on bed liner on body floor and sides

Master locking for all compartments

Recessed frame mounted bumper

Buyers or equal pintle mount with 7" plate and 8" long x 2 ½" square solid shank. Plate shall have eight (8) mounting holes. Hitch Pin to be supplied. No 2 ½" x 2" sleeve adapters will be accepted. Provide a secure retaining system for trailer safety chains if not part of factory hitch.

A combination seven (7) pin flat and a four (4) pin round trailer connector to be installed in recess of rear bumper.

A four (4) drawer storage unit shall be mounted in front curb side vertical compartment. There shall be three (3) 3-inch-deep drawers and one (1) 1 ½" deep drawer.

Install Ford factory rear vision camera kit in service body using factory prep kit.

Top Light: An ECCO 5585A amber LED light bar to be mounted on Buyers model 8895151 mount bar. Light to be wired to factory up-fitter switch and switch to be marked accordingly, "TOP LIGHT".

Bidder must supply with bid response an item-by-item list of all the service body accessories/options by manufacturer and/or sub-contractor. A blanket statement stating "we meet the intent of the spec" is not acceptable.

Vehicle must have a weight slip from certified scales with unloaded weight (tare) of chassis and the installed service body at time of delivery.

Delivery: C/O Watertown Public Works,

Attn. Pete Monaco

557 Newell St.

Watertown NY

Hours: 8a-3p M-F. Call one day in advance of delivery. 315-785-7842 or email pmonaco@watertown-ny.gov

3 of 3

10/26/2020

Rev. #1: 12/02/2020

Rev. #2: 4/6/2021